


610531 Data Sheet


24V Data Signal SPD

SURGE
PROTECTION DEVICES
LTD

- Compliant to BS EN 61643-21
- Suitable for 4 pair data signals
- Slim space-saving design
- Combined lightning and surge protection
- Din rail mountable, with integrated earthing
- Extremely low let through voltage
- Maximum cable size 2.5mm



SCAN THE QR CODE FOR THE
**INSTALLATION
INSTRUCTIONS**



Technical Data	610531
Nominal Voltage - U_n	30V
Nominal Current - I_n	1A
Lightning Impulse Current 10/350 μ s - I_{imp}	1kA
Nominal Discharge Current 8/20 μ s - I_n	10kA
Voltage Protection Level - U_p	$\leq 110V$ L-L $\leq 65V$ L-PE
Response Time - t_r	$\leq 4ns$
Bandwidth - f_b	5.1MHz
Series Impedance Per Line - R	1.8 Ω
Capacitance - C	$\leq 0.3nF$ L-L $\leq 0.6nF$ L-PE
Cross-sectional Area	2.5mm Max
Operating Temperature	-40°C to +80°C
Mounting On	35mm DIN rail

01484 851747

● info@surgedevices.co.uk ●

SURGE
PROTECTION DEVICES
LTD