

# SY2-C40XLED Data Sheet

## Type 2/3 SPD

**SURGE**  
PROTECTION DEVICES LTD



- Compliant to BS EN 61643-11
- Suitable for TNC-S, TN-S and TT installations
- LED Indication
- Pluggable replacement modules
- Remote changeover contacts as standard
- Din rail mountable
- Recommended backup fuse / MCB 32A
- Recommended cable size minimum 6mm



SCAN THE QR CODE FOR THE  
**INSTALLATION  
INSTRUCTIONS**



### Device Configurations

SY2-C40XLED/ENC

SY2-C40XLED  
Complete in  
IP Enclosure

SY2-C40XLED/ENCM

SY2-C40XLED  
Complete in  
IP Enclosure  
With 32A MCB

SY2-C40XLED/ENCMET

SY2-C40XLED  
Complete in  
Metal Enclosure

SY2-C40XLED/ENCMETM

SY2-C40XLED  
Complete in  
Metal Enclosure  
With 32A MCB

Technical Data	SY2-C40XLED
Maximum Continuous Voltage - $U_c$	275V
Nominal Discharge Current 8/20 $\mu$ s - $I_n$	20kA
Maximum Discharge Current 8/20 $\mu$ s - $I_{max}$	40kA
Voltage Protection Level - $U_p$ @ $I_n$	$\leq 1.4kV$
Voltage Protection Level - $U_p$ @ 5kA	$\leq 1.00kV$
Response Time - $t_r$	$\leq 25ns$
Tightening Torque	3Nm
Operating Temperature	-40°C to +80°C
Dimensions	4 Modules
Mounting On	35mm DIN rail
Indication of Status	LED & Remote
Classification According to BS EN 61643-11	Type 2/3

01484 851747

info@surgedevices.co.uk

**SURGE**  
PROTECTION DEVICES LTD