

SY2-DMSENCMETM

Type 2/3 SPD in an Enclosure with 100A Main Switch & 32A MCB

SURGE
PROTECTION DEVICES
LTD



- Compliant to BS EN 61643-11
- Suitable for TNC-S, TN-S and TT installations
- Window Indication
- Pluggable replacement modules
- Metal enclosure designed to BS EN 61439
- 100A double pole main switch
- 32A MCB to provide OCPD protection



SCAN THE QR CODE FOR THE
**INSTALLATION
INSTRUCTIONS**



Technical Data	SY2-D
Maximum Continuous Voltage - U_c	275V
Nominal Discharge Current 8/20 μ s - I_n	L-N 10kA N-PE 20kA
Maximum Discharge Current 8/20 μ s - I_{max}	L-N 15kA N-PE 40kA
Voltage Protection Level - U_p @ I_n	$\leq 1.5kV$
Voltage Protection Level - U_p @ 5kA	$\leq 1.00kV$
Response Time - t_a	$\leq 25ns$
Tightening Torque	L-N 1.2Nm N-PE 2Nm
Operating Temperature	-40°C to +80°C
Dimensions	1 Module
Mounting On	35mm DIN rail
Indication of Status	Flag
Classification According to BS EN 61643-11	Type 2/3

01484 851747

● info@surgedevices.co.uk ●

